

Professional Automatic Biscuit Making Machine With Custom-Design Service

Introdução detalhada :

Introduction of Automatic Biscuit Making Machine:

The biscuit production line can produce all kinds of toughness and crispy cookies. This series of production line can be arbitrarily combined according to the user's site requirements and the requirements of the cookie process, and by changing the mold and process formula can produce various kinds of high-grade cookies popular in the market, such as cream cookies, sandwich cookies, soda cookies, animal cookies, vegetable cookies and so on. And the heating methods are diversified, including electric heating, natural gas heating, heat-conducting oil heating, etc., for customers to choose at will.



Main raw materials of biscuit :1.Wheat flour 2.White Sugar 3.Eggs 4.Loosening Agent 5.Milk Powder and so on

Process Flow:Agitation of Wheat Flour Eggs,Granulated Sugar And Condiments--Dough Mixing--Biscuit Forming (printing, roll cutting)--Oven Baking--Oil Spraying--Conveys Cooling--Sorting--Sandwiching--Packaging.



Details of the Automatic Biscuit production line:

| | |
|---------------------|--|
| Production capacity | 100-2000kg/h |
| Electricity supply | Customised according to your local electricity situation. |
| Machine details | 1.Stainless steel:201, 304, 316, on request. 2.Electrical components can be ABB, Delta, Fuji, Siemens, famous brands. |
| Certificates | CE,GOST,TUV,BV,SGS |



Features of the processing line

- 1.Productivity:automated system for controlled and stable production on a continuous basis, easy and quick product change, automatic start-up, simple cleaning and maintenance procedures.
- 2.Economical: low investment, quick results.
- 3.Environmental protection: moderate output and energy saving.
- 4.Intelligent control system: PLC control of production to ensure optimum process parameters for each recipe.
- 5Automatic lubrication system can reduce power consumption and prolong service life.



Parameters of the Automatic Biscuit Production Line

| | ModelCapacity (kg/h) |
|---------|----------------------|
| LY-400 | 150-200 |
| LY-600 | 400-500 |
| LY-800 | 600-800 |
| LY-1000 | 1000-1200 |